



LEAD FBEE FORGED BBASS BALL VALVE

Committed To A Better Environment


LEHRY MAKE Lead Free & FM Approved Forged Brass Ball Valve Screwed End, which is recommended for Green Building Certification. Suitable for domestic water, Oil & Gas services,

- Female/Female threads.
- Flat lever handle with decromet Plated for Anti Rust.
- * C46500 Lead Free Forged Brass to 0.25%
- Minimum and maximum working temperatures: -20°C, 120°C in absence of steam.
- Threads ISO228 (equivalent to DIN EN ISO 228 and BS EN ISO 228).

Valve Specifications:

| SL.N. | Description | Material | Qty | | |
|-------|---------------|--|-----|--|--|
| 1 | Hex- nut | Steel Dacromet Plated to prevent Corrosion | | | |
| 2 | Handle | Steel Dacromet Plated to prevent Corrosion / Stainless Steel | 1 | | |
| 3 | Packing Nut | Cu-Alloy | 1 | | |
| 4 | Packing Gland | PTFE | 1 | | |
| 5 | O-Ring | EPDM | 1 | | |
| 6 | Stem | ½" - ¾" Forged Brass (C46500) | | | |
| | Sterri | 1" - 2" Forged Brass (C36000) | 1 | | |
| 7 | Body | Forged Brass C46500 | 1 | | |
| 8 | Seat | PTFE | 2 | | |
| 9 | Ball | 1/4"-1" Forged Brass (C46500) | | | |
| | Dali | 1 ¼" – 2" Stainless Steel 304 | 1 | | |
| 10 | Bonnet | Forged Brass (C46500) | 1 | | |

| Typical Chemical Composition of Lead-Free Brass Valves | | | | | | | | | |
|--|----|----|----|----|------|-----|-----|---------|------|
| Standard | Cu | Al | Sn | Ni | As | Pb | Fe | Zn | Ot.E |
| C46500 | 62 | 0 | 1 | 0 | 0.06 | 0.2 | 0.1 | Balance | 0.4 |



(All Dimensions are in mm)

| D | | | | | (, 2 | | a. o | •, |
|--------|----|------|------|------|------|--------|------|------|
| SIZE | DN | Α | В | С | ØD | E | F | G |
| 1/4" | 8 | 44.5 | 11.5 | 11.5 | 10 | 1/4 | 81 | 36 |
| 3/8" | 10 | 44 | 11.5 | 11.5 | 10 | 3/8 | 81 | 36 |
| 1/2" | 15 | 55 | 15 | 15 | 14.5 | 1/2" | 95 | 42.2 |
| 3/4' | 20 | 62.4 | 15.5 | 15.5 | 19 | 3/4" | 95 | 48.2 |
| 1" | 25 | 74 | 18 | 18 | 25 | 1" | 110 | 58.5 |
| 1-1/4" | 32 | 86 | 19 | 19 | 32 | 1 1/4" | 130 | 68.5 |
| 1-1/2" | 40 | 95.2 | 19.3 | 19.3 | 39 | 1 ½" | 130 | 68.5 |
| 2" | 50 | 109 | 20 | 20 | 49.5 | 2" | 161 | 88.5 |


LEHRY INSTRUMENTATION & VALVES PVT. LTD


"Lehry Chambers" #78 (Old No.51) Sembudoss Street, PB No. 1506, Parrys Chennai - 600 001.

GST No.: 33AABCL4060F1ZZ, CIN No.: U29120TN2007PTC065620.



LIV-BLV-LFBS-003





Hydraulic Test Pressure

Size: 8mm - 25mm -B.T.P.: 45 Bar S.T.P.: 30 Bar

Size: 32mm - 50mm B.T.P.: 37.5 Bar S.T.P.: 25 Bar
























: info@lehryvalves.com

Distributor Network: www.lehruvalves.com/our-distributors/ 👑 : Chennai, Jalandhar.



(g): 044 - 42510000

Dimensions

servicesupport@lehryvalves.com

